

CONNECTOR IDENTIFIER

SPECIFICATIONS SHOWN ARE INTENDED FOR IDENTIFICATION PURPOSES ONLY

1.0/2.3 SLIDE ON	PLUG	
	JACK	
1.85 mm**	MALE	
	FEMALE	
2.4 mm**	MALE	
	FEMALE	
2.92 mm*	MALE	
	FEMALE	
3.5 mm*	MALE	
	FEMALE	
7 mm	MALE	
	FEMALE	
7/16	PLUG	
	JACK	
3/4-20 TWINAX	MALE	
	FEMALE	
10 - 32	MALE	
	FEMALE	
BANANA	PLUG	
	JACK	
BNC	MALE	
	FEMALE	
REVERSE POLARITY BNC	MALE	
	FEMALE	
75 OHM BNC	MALE	
	FEMALE	

*SMA, 2.92mm, & 3.5mm CONNECTORS WILL MATE MECHANICALLY & ELECTRICALLY TO EACH OTHER.

**1.85mm & 2.4mm CONNECTORS WILL MATE MECHANICALLY & ELECTRICALLY TO EACH OTHER.

CONNECTOR IDENTIFIER

SPECIFICATIONS SHOWN ARE INTENDED FOR IDENTIFICATION PURPOSES ONLY

BNC TWINAX	PLUG	
	JACK	

C	MALE	
	FEMALE	

D SUBMINIATURE	PLUG	
	RECEPTACLE	

F	MALE	
	FEMALE	

FAKRA	PLUG	
	JACK	

FAKRA	COMPLETE KEY CODE INFO				
	CODE	JACK	PLUG	COLOR	APPLICATION
	A			BLACK	RADIO WITH PHANTOM SUPPLY
	B			WHITE	RADIO WITHOUT PHANTOM SUPPLY
C			BLUE	GPS: TELEMATICS OR NAVIGATION	
D			BORDEAUX	GSM: CELLULAR PHONE	
H			VIOLET	GPS: TELEMATICS AND NAVIGATION	
I			BEIGE	BLUETOOTH	
K			CURRY	RADIO WITH I.F. OUTPUT (ANTENNA DIVERSITY)	
Z			WATER BLUE	NEUTRAL CODING	

FME	PLUG	
	JACK	

GR874		
	HN	
HN	MALE	
	FEMALE	





























LC	MALE	
	FEMALE	

UMCX	PLUG	
	JACK	

MC-CARD		
	MCX	
MCX	PLUG	
	JACK	































CONNECTOR IDENTIFIER

SPECIFICATIONS SHOWN ARE INTENDED FOR IDENTIFICATION PURPOSES ONLY

REVERSE POLARITY MCX	PLUG	 Ø 0.15" [3.7mm]
	JACK	 Ø 0.20" [5.0mm]
75 OHM MCX	PLUG	 Ø 0.15" [3.7mm]
	JACK	 Ø 0.20" [5.0mm]
MHV	MALE	 Ø 0.57" [14.5mm]
	FEMALE	 Ø 0.44" [11.1mm]
MINI 75 OHM SMB	PLUG	 Ø 0.25 [6.4]
	JACK	 Ø 0.14 [3.7]
MINI SMP	MALE	 Ø 0.11" [2.8]
	FEMALE	 Ø 0.09" [2.2]
MINI-UHF	MALE	 3/8-24 Ø 0.45 [11.5]
	FEMALE	 3/8-24 Ø 0.31 [7.8]
MMCX	PLUG	 Ø 0.09 [2.4]
	JACK	 Ø 0.14 [3.5]
N	MALE	 5/8-24 Ø 0.80 [20.3]
	FEMALE	 5/8-24 Ø 0.55 [14.0]
REVERSE POLARITY N	MALE	 5/8-24 Ø 0.80 [20.3]
	FEMALE	 5/8-24 Ø 0.55 [14.0]
75 OHM N	MALE	 5/8-24 Ø 0.80 [20.3]
	FEMALE	 5/8-24 Ø 0.55 [14.0]
PAL	PLUG	 Ø 0.38 [9.5]
	JACK	 Ø 0.37 [9.4]
POSITIVE SNAP		 Ø 0.39 [9.9]
QMA	MALE	 Ø 0.41 [10.5]
	FEMALE	 Ø 0.19 [4.9]
RCA	PLUG	 Ø 0.37 [9.3] Ø 0.13 [3.2]
	JACK	 Ø 0.33 [8.4]
SC	MALE	 11/16-24 Ø 0.80 [20.3]
	FEMALE	 11/16-24 Ø 0.63 [15.9]

CONNECTOR IDENTIFIER

SPECIFICATIONS SHOWN ARE INTENDED FOR IDENTIFICATION PURPOSES ONLY

SHV	PLUG	 Ø 0.57" [14.5mm]
	JACK	 Ø 0.44" [11.1mm]
SMA*	MALE	 1/4-36 5/16 HEX
	FEMALE	 1/4-36 Ø 0.21 [5.3]
REVERSE POLARITY SMA	MALE	 1/4-36 5/16 HEX
	FEMALE	 1/4-36 Ø 0.21" [5.3mm]
SMA REVERSE THREAD	MALE	 1/4-36 LEFT HAND THREAD 5/16 HEX
	FEMALE	 1/4-36 LEFT HAND THREAD Ø 0.21 [5.3]
SMB	PLUG	 Ø 0.25 [6.4]
	JACK	 Ø 0.14 [3.7]
75 OHM SMB	PLUG	 Ø 0.37 [9.2]
	JACK	 Ø 0.24 [6.2]
SMC	PLUG	 #10-32 1/4 HEX
	JACK	 #10-32 Ø 0.14 [3.7]
75 OHM SMC	PLUG	 5/16-32 11/32 HEX
	JACK	 5/16-32 Ø 0.24 [6.2]
SMP	MALE	 Ø 0.15" [3.7]
	FEMALE	 Ø 0.13" [3.3]
SSMA	MALE	 #10-36 1/4 HEX
	FEMALE	 #10-36 Ø 0.16 [4.1]
SSMB	PLUG	 Ø 0.18 [4.7]
	JACK	 Ø 0.10 [2.6]
TNC	MALE	 7/16-28 Ø 0.59 [15.0]
	FEMALE	 7/16-28 Ø 0.38 [9.6]
75 OHM TNC	MALE	 7/16-28 Ø 0.59 [15.0]
	FEMALE	 7/16-28 Ø 0.38 [9.6]
REVERSE POLARITY TNC	MALE	 7/16-28 Ø 0.59 [15.0]
	FEMALE	 7/16-28 Ø 0.38 [9.6]
UHF	MALE	 5/8-24 Ø 0.70 [17.8]
	FEMALE	 5/8-24 Ø 0.55 [14.0]

*SMA, 2.92mm & 3.5mm CONNECTORS WILL MATE MECHANICALLY & ELECTRICALLY TO EACH OTHER.